



SAFETY DATA SHEET

Trade name: **LEYBONOL LVO 130** Date of issue: Nov 09, 2008

1. Identification of the substance/ mixture and of the company/ undertaking

Product identifier

Trade name: LEYBONOL LVO 130

Product description: Mineral oil with additives

Relevant identified uses of the substance or mixture and uses advised against

Uses: Vacuum pump oil, Air compressor oil

Order number: Package Size Number

> L13001 1 Liter 2 Liter L13002 L13005 5 Liter L13020 20 Liter L13099 208 Liter

Details of the supplier of the safety data sheet

Supplier Oerlikon Leybold Vacuum GmbH

> Bonner Str. 498 D-50968 Cologne

Phone +49-221-347-0 Fax +49-221-347-1250

Internet www.oerlikon.com/leyboldvacuum

E-Mail: documentation.vacuum@oerlikon.com

Emergency phone number: +49/ (0)700 24112112 (OLC)

2. Hazards identification

Health effects: This product does not present a danger of intoxication.

Environmental impact: Do not discharge this product into the environment.

Physico-chemical hazards: No specific risk of fire or explosion under normal conditions of use.

3. Composition/information on ingredients

Preparation

Chemical nature: Petroleum-derived severely refined mineral-base product in which

the polycyclic aromatic hydrocarbons (PCA or PAH) content,

measured by IP 346, is less than 3%

Substances presenting a health hazard EC No. CAS No. Content Symbol(s) R-phrases

<0,25 % R-50/53 Alkyl phenol

See section 16 for explanations of R-phrases





SAFETY DATA SHEET

Trade name: LEYBONOL LVO 130 Date of issue: Nov 09, 2008

4. First aid measures

In case of serious or persistent conditions, call a doctor or emergency medical care.

Inhalation: Inhalation of heavy concentrations of vapour, fumes or spray, may

cause mild irritation of the throat.

Transport the person into fresh air, keep warm and allow to rest.

Ingestion: Possible risk of vomiting and diarrhoea.

Do not induce vomiting to avoid the risk of aspiration into the

respiratory tract. Give nothing to drink

Skin contact: Immediately remove all soiled or stained clothing.

Wash the affected area immediately and repeatedly with soap and

water.

Eye contact: Keep eyes open and rinse immediately and repeatedly with water for

at least 15 minutes.

Aspiration: If the product is believed to have entered the lungs (in case of

vomiting, for example), take the person to hospital for immediate

care.

5. Firefighting measures

Flash point: See heading 9

Extinguishing media: - suitable:

Foam, carbon dioxide (CO2), powder.

not recommended:

Do not use water jets (stick jets) for extinguishing fire, as this may

help the spread of flames.

Specific hazards: Incomplete combustion and thermolysis may produce gases of

varying toxicity such as carbon monoxide, carbon dioxide, various

hydrocarbons, aldehydes and soot.

These may be highly dangerous if inhaled. Vapours can build explosive mixtures with air.

Vapours are heavier than air and may spread on the ground to

sources of ignition.

Protective measures for fire-fighters: Insulated breathing apparatus must be worn in confined premises

with heavy concentrations of fumes and gases.

Other: All combustion residues and contaminated water from fire-fighting

should be disposed of according to local regulations.

6. Accidental release measures

See sections 8 and 13.

Personal protection: Ensure good ventilation.

Remove sources of ignition. Do not smoke.





SAFETY DATA SHEET

Trade name: LEYBONOL LVO 130 Date of issue: Nov 09, 2008

After spillage / leakage: - On land:

Surfaces on which the product has been spilled may become

slippery.

Do not allow the product to enter sewers or rivers or contaminate the

soil.

Recover with mechanical means such as pumps and skimmers.

- On water:

Floating absorbant material, then mechanical recovery.

If the product is spilt into rivers or sewers, notify the authorities of the

possible presence of surface effluent.

Spill cleanup methods: - Recovery:

Contain and collect the spilled product. Use sand on the surfaces

concerned if necessary.

Contain and collect the spilled product with sand or any other inert

absorbent material.

In the event of a major spill, inform the relevant authorities if the situation cannot be brought under control rapidly and efficiently.

- Elimination:

Dispose of waste in compliance with regulations.

Avoid discharge of the material in a stream or a sewer or cause

ground contamination.

7. Handling and storage

Handling

Prevention of user exposure: Ventilate extensively if the formation of vapours, fumes, mists or

aerosol is a risk.

Make all the necessary arrangements in order to reduce exposure

risk, notably to products in use or to wastes.

Keep away from combustible substances; keep away from food and

beverages.

Prevention of fire and explosion: Empty containers may contain flammable or explosive vapours.

There is a fire hazard associated with rags, paper or any other material used to remove spills which become soaked with product. Avoid accumulation of these: they are to be disposed off safely after

use.

Precautions: Avoid static electricity build up with connection to earth.

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on

joint failure, for example).

Storage

Technical measures: Make the necessary arrangements to prevent water and soil

pollution.

Storage precautions: - Suitable:

Store at ambient temperature, protected against contact with water

and moisture, and away from any source of ignition.

Keep containers closed when not in use

- To be avoided:

Do not store exposed to the elements.

Incompatible products: Dangerous reaction with strong oxidizing agents.





SAFETY DATA SHEET

Trade name: LEYBONOL LVO 130 Date of issue: Nov 09, 2008

Packaging materials: - Recommended:

Use only hydrocarbon-resistant containers, joints, pipes, etc.

Keep in original container if possible.

8. Exposure controls/ personal protection

Technical measures: Use the product in a properly ventilated atmosphere.

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not suffocating and/or wear recommended

equipment.

Occupational exposure limit: . oil mist : 10mg/m3, for 15 minutes

. oil mist : 5mg/m3, for 8 hours

Hand protection: Impermeable hydrocarbon-proof gloves.

recommended material: nitrile, neoprene.

The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from

the manufacturer of the protective gloves themselves.

The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength

and duration of exposition).

Before choosing suitable gloves, it is recommended that the user

tests the gloves.

Eye protection: Goggles, in case of risk of splashing.

Skin and body

(other than the hands) protection: As required, wear a face mask, hydrocarbon-proof clothing, and

safety boots (when handling drums).

Don't wear rings, watches or anything similar which can retain the

product and may give rise to skin conditions.

Hygienic work practices: Avoid prolonged and repeated contact with the skin, especially with

used or waste product

Immediately remove all soiled or stained clothing.

If the product comes into contact with the skin, wash the affected

area immediately and copiously with soap and water.

Do not use abrasives, solvents or fuels.

Do not dry hands with rags that have been contaminated with

oroduct.

Do not put product contaminated rags into workwear pockets.

Do not eat, drink or smoke whilst handling the product.

9. Physical and chemical properties

Appearance: Liquid.

Colour: Yellow to amber.
Odour: Characteristic for oil.

Density/specific gravity: 880 kg/m3

Temperature ($^{\circ}$ C) 15 > 200 $^{\circ}$ C OC (Open cup).

Flash point: > 200 °C OC (Open cup) Température d'auto-inflammation: > 250 °C (ASTM E 659)

Partition coefficient (log Pow): Log Pow > 6 Temperature (°C) 20

68 mm2/s

Temperature (°C) 40

Viscosity:





SAFETY DATA SHEET

Trade name: LEYBONOL LVO 130 Date of issue: Nov 09, 2008

10. Stability and reactivity

Stability: The product is stable at normal storage, handling and use

temperatures.

Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points,

flames, static electricity

Materials to avoid: Avoid contact with strong oxidizers

Hazardous decomp. products: Incomplete combustion and thermolysis produces potentially toxic

gases such as carbon monoxide, carbon dioxide, various

hydrocarbons, aldehydes and soot.

11. Toxicological information

Acute toxicity / Local effect

Inhalation, comments: Not classified according to the criteria of classification in force.

Inhalation of high concentrations of vapour or aerosols may cause

irritation of the upper respiratory tract.

Skin contact, comments:Not classified according to the criteria of classification in force.

In case of ingestion, comments: In case of ingestion of small quantities, no important effect observed.

in case of ingestion of larger amounts: abdominal pain, diarrhea, ...

Chronic toxicity or long-term toxicity

Skin contact: Characteristic skin affections (oil blisters) may develop following

prolonged and repeated exposure through contact with stained

clothing.

Sensitization: To our knowledge, the product does not cause aggravated

sensitivity.

Carcinogenicity: This product is not regarded as carcinogenic.

12. Ecological information

Comments about ecotoxicity: Experimental data on the finished product are not available.

It is considered to present a little danger for aquatic life.

no information available for used product

Mobility: - Air:

there is a slow loss by evaporation.

- Soil:

Given its physical and chemical characteristics, the product generally

shows little mobility in the ground.

- Water:

The product is insoluble; it spreads on the surface of the water

Persistence and degradability: No experimental information about the finished product.

However the "mineral oil" fraction of the new product is intrinsically

biodegradable.

Some components of the product may not be biodegradable.





SAFETY DATA SHEET

Trade name: LEYBONOL LVO 130 Date of issue: Nov 09, 2008

13. Disposal considerations

Waste disposal: Dispose of in a safe manner, in accordance with local regulations.

If need be, collection by an authorised waste contractor and

regeneration or incineration at an approved installation.

Waste class: 13 02 05

The waste classification is dependant on the composition of the

product at the time of disposal.

The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct

specification of the waste. The specification of the waste

classification should be in arrangement with the authorised waste

disposal company.

Disposal of contaminated packaging: Proceed in compliance with the prevailing regulations.

14. Transport information

Not concerned by the transport regulations below

Road (ADR) / Rail (RID)

Transport by barge (ADNR)

Marine (IMO-IMDG)

Air (ICAO/IATA)

15. Regulatory information

Not applicable

Risk phrases: None

Safety phrases: None

EU directives: Hazardous preparations directive 1999/45/EC modified (Directive

2001/60/EC).

Social Security code: - Art. L 461-6, Art. D.461-1, annexe A, n° 601

Table of occupational illnesses and diseases No. 36

Labor code: - Art. R 241-50, decree of 07.11.1977 (special medical surveillance).

16. Other information

Explanations of R-phrases in section 2: R-50/53 Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.





SAFETY DATA SHEET

Trade name: LEYBONOL LVO 130 Date of issue: Nov 09, 2008

Date of issue: 2008-11-09

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.