

MATERIAL SAFETY DATA SHEET

CMP 57 Mechanical Pump Fluid



HMIS RATING

Health: 1 Flammability: 1 Reactivity: 0 Special: X

SECTION 1 -- LOCATION

Location: 6005 Alliance Road N.W.
 Malvern, Ohio 44644
Telephone: 330-863-1121
Date Prepared: January 1, 2008

SECTION II -- HAZARDOUS INGREDIENTS/IDENTITY

Hazardous Component(s) Chemical and Common Name(s)...Severely Hydrotreated Paraffinic oil

Exposure Limit

CAS No. 64742-54-7 100% 5mg/m3 Oil Mist

To the best of our knowledge, the above listed component(s) is not hazardous according to OSHA (1910.1200) or one or more State Right-to-Know lists.

SECTION III -- PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance and Odor:	Light Yellow to Amber liquid; mild odor
Specific Gravity @ 22 (C):	.88
Vapor Pressure @ 25 (C):	3 x 10 ⁻⁶ Torr
Vapor Density (Air=1):	Not Applicable
Solubility in Water:	Insoluble
Reactivity in Water:	Not Applicable
Melting Point:	Not Applicable

SECTION IV -- FIRE & EXPLOSION DATA

Flash Point:	482° (F) 250° (C)	Method Used: C.O.C.
Flammable Limits (%):	No Data Available	
Extinguishing Media:	CO ₂ , Dry Chemical, Foam and Water Fog	

Special Fire Fighting Procedures: For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion and oxygen deficiency.

Unusual Fire and Explosion Hazards: Normal combustion forms Carbon Dioxide and water vapor. Incomplete combustion can produce Carbon Monoxide.

CAUTION: DO NOT USE PRESSURE TO EMPTY DRUM OR EXPLOSION MAY RESULT.

THE INFORMATION IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED, IS MADE

Page 1

MATERIAL SAFETY DATA SHEET

SECTION V-PHYSICAL HAZARDS (REACTIVITY DATA)

Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Excessive heat.
Hazardous Polymerization:	Will not occur
Incompatibility (Materials to Avoid):	May react with strong oxidizing agents such as Chlorates, Nitrates, peroxides, etc.
Hazardous Decomposition Products:	Excessive heat may produce Carbon Monoxide, Carbon Dioxide, Aldehydes and Ketones, combustion products of Nitrogen and Sulfur.

SECTION VI-HEALTH HAZARDS

Eyes:	This substance is not expected to cause prolonged or significant eye irritation. This hazard evaluation is based on data from similar materials.
Skin:	This substance is not expected to cause prolonged or significant skin irritation. This hazard evaluation is based on data from similar materials.
Inhalation:	If inhaled, this substance is considered practically non-toxic to internal organs. This hazard evaluation is based on data from similar materials.
Ingestion:	If swallowed, this substance is considered practically non-toxic to internal organs. This hazard evaluation is based on data from similar materials.

Chemical Listed as Carcinogen or Potential Carcinogen:

IARC Monographs: No

OSHA: No

National Toxicology Program: No

Routes of Entry

Inhalation:	This material is not expected to be an immediate inhalation problem. Remove to fresh air. Obtain medical assistance if difficult breathing.
Eyes:	Flush eyes with fresh water for 15 minutes. Remove contact lenses if worn. No first aid procedures are required.
Skin:	No first aid procedures are required. As a precaution, wash skin thoroughly with soap and water. Remove and wash contaminated clothing.
Ingestion:	No adverse effects are expected. If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur. Consult Medical Personnel before inducing vomiting.

SECTION VII-SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be taken in Handling and Storage: Minimum feasible handling temperatures should be maintained. Periods of exposure to high temperature should be minimized. Water contamination should be avoided.

Steps to be taken in Case of Release or Spill: Ventilate area, Avoid breathing vapor. Use self-contained breathing apparatus or supplied air for large spills or confined areas. Contain spill if possible. Wipe up or absorb on suitable material and shovel up. Prevent entry into sewers and waterways.

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED IS MADE.

Page 2

CAMBRIDGE MILL PRODUCTS, INC.; 3049 ALLIANCE RD. N.W.; MALVERN, OH 44644 PH: 330-863-1121

MATERIAL SAFETY DATA SHEET

SECTION VII-SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURS (CONT'D.)

Waste Disposal Methods (Consult Federal, State, and Local Regulations): Under RCRA, it is the responsibility of the user of products to determine at the time of disposal whether product meets RCRA criteria for hazardous waste. This is because uses, transformation, mixture, processes, etc., may tender the resulting materials hazardous.

SECTION VIII-SPECIAL PROTECITON INFORMATION/CONTROL MEASURES

- Respiratory Protection: None required if exposures are within permissible concentrations of 5.0mg/m3 of air for mineral oil mist averaged over an eight-hour daily exposure (ACGIH 1984-85).
- Ventilation: Normal.
- Protective Gloves: Impervious gloves when prolonged contact cannot be avoided.
- Eye Protection: Chemical type goggles/fact shield.
- Other Protective Equipment: None considered necessary at this time.
- Work/Hygienic Practices: Employees should exercise reasonable personal cleanliness.

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and **we expressly disclaim all warranties of every king and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product.** Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

ATTENTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to pen flam or heat. Keep container closed and drum bungs in place.

REGULATORY INFORMATION:

D.O.T. SHIPPING NAME:	NOT APPLICABLE
D.O.T HAZARD CLASS:	NOT APPLICABLE
D.O.T. IDENTIFICATION NUMBER:	NOT APPLICABLE

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIES, IS MADE.

