

# MATERIAL SAFETY DATA SHEET FOR: DIRECTORR® 8995G GOLD VACUUM PUMP OIL

**HMIS Rating:** Health: 0 Flammability: 1 Reactivity: 0 Special: X

## **SECTION 1 - IDENTIFICATION**

Chemical Name: Synthetic Hydrocarbon

Synonyms: DIRECTORR® 8995G Gold Vacuum Pump Oil

Formula: NA (Product is refined naturally occurring mixture)

Manufacturer's Name: Welch Rietschle Thomas

7301 North Central Ave. Skokie, IL 60077

March 10, 2004

Telephone Number for

Date Prepared:

General Information: (847) 676-8800

# **SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY**

Exposure Limits in Air

Component CAS No. OSHA PEL ACGIH TVL

Synthetic Hydrocarbon 68037-01-4 NO NO

To the best of our knowledge, the above listed component is not hazardous according to OSHA (1910.1200) or one or more state right-to-know lists.

# **SECTION 3 - PHYSICAL AND CHEMICAL CHARACTERISTICS**

Appearance and Odor: Light Straw Color, Slight Odor

Specific Gravity @ 22°C (72°F) (Water = 1): 0.83 @ 22°C (72°F)

Vapor Pressure, Torr @ 25°C: 1x10-7
Vapor Density (Air = 1): N/A
Water Solubility: Insoluble
Boiling Point (ASTM D-86 Method): 445°F
Reactivity in Water: N/A
Melting Point: N/A

# THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIES, IS MADE.



## SECTION 4 - FIRE AND EXPLOSION HAZARDS DATA

Flash Point: 480°F 249°C

Method Used: COC

Flammable Limits: Upper: N/D Lower: N/D

Extinguishing Media: Use water spray, dry chemical, foam or carbon dioxide.

Special Fire Fighting Procedures: For fires involving this material, do not enter any enclosed or

confined space without proper protective equipment, including self-

contained breathing apparatus.

Unusual Fire and Explosion Hazards: Do not weld, heat or drill container. Residue may ignite with

explosive violence if heated sufficiently.

CAUTION: DO NOT USE PRESSURE TO EMPTY DRUM,

OR EXPLOSION MAY RESULT.

# **SECTION 5 - PHYSICAL HAZARDS (REACTIVITY DATA)**

Stability: Stable under normal conditions.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Avoid heating to decomposition. User is advised to have a

safety expert evaluate the specific conditions of use.

Incompatibility (Materials to Avoid): N/D

Hazardous Decomposition Products: Includes Oxides of Carbon.

## **SECTION 6 - HEALTH HAZARD DATA**

Eyes: Expected to cause no more than minor eye irritation.

Skin: Expected to cause no more than minor irritation following prolonged

or frequent repeated contact

Inhalation: Inhalation of Oil mist vapors at elevated temperatures may cause respiratory irritation.

Ingestion: Ingestion harmful if aspirated into the lungs. Do not induce vomiting.

Chemical Listed as Carcinogen or Potential Carcinogen:

IARC Monographs: No OSHA: No National Toxicology Program: No

#### SIGNS AND SYMPTOMS OF EXPOSURE

**Primary Routes** 

of Exposure: Inhalation, skin or eye contact, and ingestion.

#### FIRST AID MEASURES

If Inhaled: Remove to fresh air. If victim has stopped breathing, give artificial respiration. Seek

medical attention.

In Case of Eye Contact: Immediately flush eyes with plenty of cool water for 15 minutes.

Do not let victim rub eyes.

In Case of Skin Contact: Wash affected area thoroughly.

If Swallowed: <u>Do not induce vomiting.</u> If victim is conscious and able to swallow, give water to

dilute, do not give sodium bicarbonate, fruit juices, or vinegar. See medical attention.

#### THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIES, IS MADE.

Revision Date: 02/10/04	Rev. 2	<b>P/N: 67-0293A</b> 2 of 3
130,7151011 17410. 02/10/07	NCV. Z	1/11. 0/-02/3/1 2013



## **SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE**

Storage and Handling Precautions: Minimum feasible handling temperatures should be maintained.

Periods of exposure to high temperature should be minimized.

Waste Disposal Method: Under RCRA, it is the responsibility to the user of products to

determine at the time of disposal whether product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixture, processes, etc. may render the resulting

material hazardous.

Action to Take for Spills or Leaks: Wear appropriate respiratory protection and protective clothing

as described below. Contain spilled material. Transfer to secured containers. Collect using absorbent media. In the event of an uncontrolled release of this material, user should determine if release is reportable under applicable laws and regulations

under RCRA.

## **SECTION 8 - CONTROL MEASURES**

Ventilation: Mechanical ventilation recommended.

Respiratory Protection: NIOSH approved organic vapor respiratory when exposed to vapor

from heated material

Protective Gloves: Impervious gloves when prolonged contact cannot be avoided.

Eye Protection: Chemical type goggles/face shield.

Protective Clothing: Impervious gloves when prolonged contact cannot be avoided.

Other Protective Measures: None considered necessary at this time.

Work/Hygienic Practices: Employees should exercise reasonable personal cleanliness.

All statements, information, and data provided in this Material Safety Data Sheet are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied on our part. Users should make their own investigations to determine the suitability of the information of products for their particular purpose.

ATTENTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable or reactive materials. Cutting or welding of empty containers might cause fire, explosion, or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep containers closed and drum bung in place.

### THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIES, IS MADE.