



ExploraVAC System Data Sheet

Part Number	P1012091	Basic Vacuum Test System
		Comments/Notes
System Platform	ExploraVac Base System	
Vacuum Chamber		
Size	20 x 20 x 20 in (51 x 51 x 51 cm)	Internal dimensions
Material	304 Stainless Steel	Welded chamber
Volume	4.6 cu ft (130L)	Internal volume
Vacuum Pumping		
Rough Pump	Edwards nXDS20i	Dry scroll pump
Roughing Speed	13.0 cfm (22.0 m ³ hr ⁻¹) **	
Turbo Pump	N/A*	
Turbo Speed	N/A*, **	
Vacuum Gauges		
Gauge Models	Granville 475 Single Convectron	
Measurement Range	1x10 ⁻⁴ Torr to atmosphere	
Control Interface	Integrated Button Panel	Illuminated tactile controls
System Pressure		
Operating Pressure	2x10 ⁻² Torr to 1 atm	
Altitude Control	N/A*	
Thermal Platen		
Temperature Range	N/A*	
Heating Power	N/A*	
Cooling Power	N/A*, **	
System Package		
System Weight	760 lbs (345kg)	Approximate dry weight
System Size	33 x 36 x 69 in (84 x 91 x 175 cm)	
Onboard Air Source	150 psi regulated, 2 gallon capacity	Power for pneumatic valves
System Power		
Input Voltage	208-240 VAC w/Neutral, Single Phase	
Input Frequency	50-60 Hz	
Input Current	20 Amps (at max load)	
Recommended Service	20 Amps, 220 Volts	
Operating Environment		
Temperature	50 °F to 86 °F (10 °C to 30 °C)	Ambient room temp
Humidity	5% - 80%	
Connections		
Chamber Vent	KF-16 (to Atmosphere)	Chamber vents to atmosphere
Chamber Gas Purge	N/A*	
Pump Exhaust	KF-25	Connectable to facility exhaust

*Options marked as N/A not included in this system build

**Peak capability shown. Refer to detailed option specifications for performance curve data.