



## ExploraVAC MAX System Data Sheet

<b>Part Number</b>	P1012103	Entry Level Vacuum Test System
--------------------	----------	--------------------------------

		<b>Comments/Notes</b>
<b>System Platform</b>	ExploraVac MAX System	
<b>Vacuum Chamber</b>		
Size	24 x 24 x 24 in (30 x 30 x 30 cm)	Internal dimensions
Material	304 stainless steel	Welded chamber
Volume	8 cu ft (226 L)	Internal volume
<b>Vacuum Pumping</b>		
Rough Pump	Edwards nXDS10i	Dry scroll pump
Roughing Speed	6.7 cfm (11.4 m <sup>3</sup> hr <sup>-1</sup> ) **	
Turbo Pump	N/A*	
Turbo Speed	N/A*, **	
<b>Vacuum Gauges</b>		
Gauge Models	Granville 475 single Convector	
Measurement Range	1x10 <sup>-4</sup> Torr to atmosphere	
<b>Control Interface</b>	Integrated touch screen	AutoExplor Software
<b>System Pressure</b>		
Operating Pressure	5x10 <sup>-3</sup> Torr to 1 atm	
Altitude Control	N/A*	
<b>Thermal Platen</b>		
Temperature Range	N/A*	
Heating Power	N/A*	
Cooling Power	N/A*, **	
<b>Chamber Heating</b>		
Temperature Range	N/A*	
Heating power	N/A*	
<b>System Package</b>		
System Weight	1350 lbs (603 kg)	Approximate dry weight
System Size	33 x 36 x 80 in (84 x 91 x 203 cm)	
<b>Onboard Air Source</b>	150 psi regulated, 2 gallon capacity	Power for pneumatic valves
<b>System Power</b>		
Input Voltage	208-240 VAC, 50-60 Hz	w/Neutral, Single Phase
Input Current	20 Amps (at max load)	
Recommended Service	20 Amps, 220 Volts	
<b>Operating Environment</b>	50 °F to 86 °F (10 °C to 30 °C) 5% - 80% Humidity	Ambient room conditions
<b>Connections</b>		
Chamber Vent	KF-16 (to atmosphere)	Chamber vents to atmosphere
Chamber Gas Purge	N/A*	
Pump Exhaust	KF-25	Connectable to facility exhaust

\*Options marked as N/A are not included in this system build.

\*\*Peak capability shown. Refer to detailed option specifications for performance curve data.

